Atch 014

# NOTICE OF REVISION (NOR)

THIS REVISION DESCRIBED BELOW HAS BEEN AUTHORIZED FOR THE DOCUMENT LISTED

1. DATE (YYYYMMDD): 290210

Form Approved OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 2 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.
PLEASE DO NOT RETURN YOUR COMPLETED FORM TO THE ADDRESS. RETURN COMPLETED FORM TO THE GOVERNMENT ISSUING CONTRACTING OFFICER FOR THE CONTRACT/PROCURING ACTIVITY NUMBER LISTED IN ITEM 2 OF THIS FORM.

2. PROCURING ACTIVITY NO.: R2G2001

3. DODAAC:

4. ORIGINATOR

a. TYPED NAME (First, Middle Initial, Last): Gerard M. Eilert

b. ADDRESS (Street, City, State, Zip Code): U.S. Army TACOM-ARDEC, AMSTA-AR-FSA-M, Bldg 61s, Picatinny Arsenal, NJ 07806

5. CAGE CODE: 19200

6. NOR NO.: 001

7. CAGE CODE: 19200

8. DOCUMENT NO.: P9235210

9. TITLE OF DOCUMENT: Fuze, Grenade, Hand, Practice, M228

10. REVISION LETTER: a. CURRENT: M; b. NEW:

11. ECP NO.: R2G2001

12. CONFIGURATION ITEM (OR SYSTEM) TO WHICH ECP APPLIES: Grenade, Hand; Practice, Delay, M69

13. DESCRIPTION OF REVISION

Change
Notes: 4

Delete in its entirety

Replace with

FUZE LESS IGNITER TO BE SUBJECTED TO THERMAL SHOCK TEST C7 FOLLOWED BY JOLT TEST A1 AND JUMBLE TEST A2 PER MIL-STD-331. LOW AND HIGH TEMPERATURE FOR SHOCK TEST SHALL BE MINUS 30°F AND 140°F RESPECTIVELY AND LENGTH OF EXPOSURE TO EACH TEMPERATURE SHALL BE 2 HOURS. TEST SHALL CONTINUE FOR TWO CYCLES. EACH CYCLE CONSISTING OF 1 HIGH TEMPERTURE AND 1 LOW TEMPERATURE EXPOSURE. FUZE THEN TO BE SUBJECTED TO FUNCTIONING TEST EITHER WITH OR WITHOUT IGNITER. NEITHER PRIMER NOR PRIMER HOLDER ASSEMBLY SHALL BLOW OUT IN FUNCTIONING TEST.

14. THIS SECTION FOR GOVERNMENT USE ONLY

a. (If any)
- [X] (1) Existing document implemented by this NOR may be used in manufacture.
- [ ] (2) Revised document must be received before manufacturer may incorporate this change.
- [ ] (3) Correction of errors discovered during review of existing and/or revised documents.

b. ACTIVITY AUTHORIZED TO APPROVE CHANGE FOR GOVERNMENT: SMCCM-ARDEC, AMSTA-AR-FSA-S

c. TYPED NAME (First, Middle Initial, Last):

d. TITLE: ARTHUR J. HEVORDAHER, Chief, PBAC Prod & Log Eng Sp

e. SIGNATURE: Team

f. DATE SIGNED (YYYYMMDD): 2002. 12 11

14a. ACTIVITY ACCOMPLISHING REVISION: AMSTA-AR-FSA-M

b. REVISION COMPLETED (Signature):

c. DATE SIGNED (YYYYMMDD):

DD FORM 1695, AUG 98 (EG) — PREVIOUS EDITION MAY BE USED. — Designed using Perform Pro, WHS/DIOR, Aug 98

Distribution Statement A. Approved for Public Release; Distribution is unlimited.